

[Substitute Specification Showing Interlineations]

THERMOSTATIC CONTROLLER AND CIRCUIT TESTER

5 Background of the Invention:

Field of the Invention:

~~This~~ The present device is designed for ~~exclusive~~ use and deployment in the "HEATING VENTILATING AND AIR CONDITIONING" (HVAC) industry and relates to a thermostatic controller and
10 circuit tester, and more particularly, to a portable
thermostatic controller and circuit tester. This utility device along with its attributes, is the product of years of working and tolerating the shortcomings of current test equipment available to the trade.

15

Package units located on roofs or on the sides of buildings,
air handlers and water cooled heat pumps located in dark
closets and sometimes attics, sometimes pose a challenge to
the technician, mainly because of their accessibility by
20 ladders only.

This sometimes requires the technician to ascend and descend
ladders to test the repairs made, by operating the
thermostat, or he can shout down to someone (if available) to
25 operate the thermostat.

Summary of the Invention:

~~This product as illustrated in FIG. 1 is designed~~ A portable
thermostatic controller and circuit tester is provided for
5 the trades needs and demands as envisaged by the inventor, of
whom, is a HVAC technician. This device is time saving and
space saving, while giving the technician greater flexibility
and latitude when working alone.

10 In one embodiment of the present invention, the thermostatic
controller and circuit tester ~~The device~~ comprises two
separate circuits that performs independently of each other.
The two circuits are never integrated, except when using the
circuit tester to check continuity of the controller circuit,
15 whenever necessary. In another embodiment of the present
invention, the portable thermostatic controller device
comprises at least a controller circuit and a built in
flashlight.

20 The ~~THERMOSTATIC CONTROLLER AND CIRCUIT TESTER~~ thermostatic
controller and circuit tester, in accordance with the present
invention, is ideal for fieldwork, in the workshop and
classroom demonstration. But nowhere does its attributes
comes into its own, than in fieldwork. That is when its
25 usefulness is highlighted due to its diverse working

environment. ~~Package units located on roofs or on the sides of buildings, air handlers and water cooled heat pumps located in dark closets and sometimes attics, do sometimes pose a challenge to the technician, mainly because of their~~
5 ~~accessability by ladders only.~~

~~This sometimes requires the technician to ascend and descend ladders to test the repairs made, by operating the thermostat, or he can shout down to someone (if available) to~~
10 ~~operate the thermostat.~~

With a thermostatic controller and circuit tester, in accordance with the present invention, "THERMOSTATIC-CONTROLLER AND CIRCUIT TESTER" all he a technician needs to
15 do is switch the thermostat to off and switch off the line voltage disconnect switch located on or nearby the unit, to off. Using the device of the present invention, the technician can then ~~Then~~ proceed to troubleshoot and make repairs. When repairs ~~are~~ have been completed, a

20 thermostatic controller and circuit tester, in accordance with the present invention, via a set of the alligator clips, are is then attached to the low voltage connector block or thermostat wire connections by removing wire nuts the twist-on wire connectors and exposing the bare wires. ~~Then go~~
25 ~~ahead and operate the~~ The controller circuit can then be

operated by pressing the switches one to four located on the
face thereof.

With the portable device of the present invention, the ~~The~~
5 technician avoids unnecessary trips to the thermostat
location, saves time and energy and most of all he is now
very independent of extra tools and helping hands.

Brief Description of the Drawing:

10 FIG. 1 is an isometric view of a portable thermostatic
controller and circuit tester in accordance with one
particular embodiment of the present invention.

FIG. 2 is a schematic circuit diagram of a controller circuit
15 of the thermostatic controller and circuit tester, in
accordance with one embodiment of the present invention.

FIG. 3 is a schematic circuit diagram of a test circuit of
the thermostatic controller and circuit tester, in accordance
20 with one embodiment of the present invention.

FIG. 4 is a schematic diagram of the controller circuit of
FIG. 2 shown in use, connected to a connector block or
thermostat wires of an HVAC unit, in accordance with the one
25 embodiment of the present invention.

FIG. 5 is a schematic diagram of a circuit tester in accordance with one embodiment of the present invention.

5 FIG. 6 is a diagram of the circuit tester of FIG. 5 being in use according to one embodiment of the present invention.

FIG. 7 is a partial exploded view of a portable thermostatic controller and circuit tester in accordance with one
10 embodiment of the present invention.

FIG. 8 is a front perspective view of a portable thermostatic controller and circuit tester in accordance with one particular embodiment of the present invention.

15 Referring now to the figures of the drawing in detail and first, particularly, to Fig. 1 thereof, there is seen a

Description of the Preferred Embodiments:

Referring now to FIGS. 1 - 7, there is shown a portable
20 thermostatic controller and circuit tester 10 in accordance with a preferred embodiment of the present invention.

Once a technician has switched the thermostat of an HVAC unit to off and switched off the line voltage disconnect switch
25 located on or nearby the unit, the portable thermostatic

controller and circuit tester 10, can be used to troubleshoot
the unit and to make repairs. Once repairs are completed,
the alligator clips 22, 24, 26 and 28 are attached to the low
voltage connector block or thermostat wire connections (as
5 shown more particularly in Fig. 4) by removing twist-on wire
connectors and exposing the bare wires. The technician can
then go ahead and operate the controller circuit 70 of the
portable thermostatic controller and circuit tester 10 by
pressing the switches SW1, SW2, SW3, SW4, labeled in FIG. 1
10 as power, fan, cool and heat, respectively.

The Controller Circuit and how it Works

~~Refer~~ Referring now more particularly to FIG. 2. The
15 controller circuit 70 is basically a kind of portable
thermostat without the sensor and circuit board. There is no
PC board of semiconductor components involved in its
circuitry. It consists of four push on/push off switches SW1,
SW2, SW3, SW4 arranged in parallel and soldered to four color
20 coded wires, RED, GREEN, YELLOW, WHITE, 30 inches long from
each switch with alligator clips 22, 24, 26, 28 soldered to
the other ends of each wire RED, GREEN, YELLOW, WHITE.

With reference to FIG. 2, switches ~~1-4~~SW1 - SW4 are all in
25 the normally open position, therefore making the circuit 70

off and inactive. In FIG. 4 switches ~~1 and 2~~ SW1 and SW2 are engaged in the ON mode. Both switches are now energized.

Switch ~~[[1]]~~ SW1 passes low voltage power from the secondary output of the transformer T1 onto Switch ~~[[2]]~~ SW2 which in turn passes the voltage to Relay ~~[[1]]~~ RLY1. Relay ~~[[1]]~~ RLY1 would then be energized and closed. This allows line voltage to flow via Relay ~~[[1]]~~ RLY1 to the load. Switch ~~[[2]]~~ SW2 is connected to the green wire, which in HVAC trade is universally associated with the fan or blower. As

10 particularly shown in FIG. 4, switches 3 and 4 switches SW3 and SW4 are still in the open position, but when energized and closed via Switch ~~[[1]]~~ SW1 , they perform their roles the same way as Switch ~~[[2]]~~ SW2.

15 Table 1 is a table showing the switch positions for different controller applications.

<u>APPLICATION</u>	<u>MODE</u>	<u>Red</u> <u>SW1</u> <u>POWER</u>	<u>Green</u> <u>SW2</u> <u>FAN</u>	<u>YELLOW</u> <u>SW3</u> <u>COMP</u>	<u>WHITE</u> <u>SW4</u> <u>HTR</u> <u>SOL</u>	<u>COMMENTS</u>
<u>HEAT PUMP</u>	<u>COOL</u>	● —	● —	● —	● —	<u>SOLENOID</u> <u>SWITCHES</u> <u>REVERSING VALVE</u> <u>TO COOLING MODE</u>
<u>HEAT PUMP</u>	<u>HEAT</u>	● —	● —	● —		<u>SOLENOID</u> <u>INACTIVE</u> <u>REVERSING VALVE</u> <u>PRE-SET FOR</u> <u>HEATING</u>
<u>SPLIT</u> <u>SYSTEM</u>	<u>COOL</u>	● —	● —	● —		

<u>SPLIT</u> <u>SYSTEM</u>	<u>HEAT</u>	● —	● —		● —	
-------------------------------	-------------	--------	--------	--	--------	--

Table 1

The ~~THERMOSTATIC CONTROLLER AND CIRCUIT TESTER~~ thermostatic controller and circuit tester 10 can also be used to

5 determine if a thermostat is defective or if there is a broken wire between the thermostat and the units that ~~comprises~~ comprise the air conditioning system. To do so, simply switch off the thermostat breaker or the disconnect switch, then dismantle thermostat from wall. Disconnect
10 thermostat wires from their terminals. Now connect the controllers alligator clips 22, 24, 26, 28 to the ends of the exposed thermostat wires, RED to RED, YELLOW to YELLOW or BLUE, GREEN to GREEN and WHITE to WHITE. Now go ahead and switch on the breaker or the disconnect switch. Operate the
15 system by means of the controller's push on/push off switches ~~1-4~~ SW1 - SW4 of the thermostatic controller and circuit tester 10. The technician then makes his diagnosis based upon the unit's performance and his findings.

20 The Test Circuit and how it Works

In FIG. 5 there is an electronic circuit board (85 of Fig. 7) as part of a variable circuit. This circuit comprises a light source L3 (which is directed from the top face of the device

10, away from the front face, as shown in FIG. 1), a buzzer BUZZER for checking continuity and a tiny printed circuit board that consists of two bias resistors R1 and R2 and two neon lamps L1 and L2. ~~This latter~~ The test circuit 80 is
5 designed for testing AC voltage. The light L3 and buzzer BUZZER section of this circuit are powered by the two 1.5 VDC batteries 82, 84 =3 VDC. A DPDT slide switch SW5 (on/off) is an integral part of this circuit and is used to switch roles.

10 ~~Refer~~ Referring now to Figs. 1 - 7, the ~~to FIG. 5.~~ The circuit tester 80 and light source are operated as follows: the two 1.5 VDC batteries 82, 84 =3 VDC are arranged in series. A 3 VDC pre-focused flashlight bulb L3 along with a momentary switch ~~(SW1)~~ SW6 arranged in parallel, is fed by
15 the batteries. The momentary switch ~~(SW1)~~ SW6 was chosen, so as to save battery energy, by not being unintentionally left on for long periods.

This is the built-in flashlight operated by Switch ~~[[1]]~~ SW6.

20 The circuit 80 extends to a DPDT slide switch ~~(SW2)~~ SW5.

From switch ~~[[1]]~~ SW6 a 3 VDC buzzer BUZZER and a 315 MA quick blow fuse FUSE (for buzzer protection) are arranged in series and connected to one end of switch ~~[[2]]~~ SW5 at

25 position "A".

When switch SW5 is switched to position "A", the circuit 80 is now in the mode for continuity test. The middle tags of switch SW5 are connected to two output
5 test lead jacks 14 and 16. As illustrated at the bottom of FIG. 5, when the circuit tester via the detachable test leads 30a, 30b and probes 32, 35 are brought into contact with a metallic object such as a fuse 50, the buzzer should emit an audible sound heard through the device casing holes (12 of
10 FIG. 1) if the fuse 50 is good.

On the other side of switch SW5, the switch is now engaged in position "B" as illustrated in FIG. 6. This section of the circuit 80 ~~comprised of~~ includes series and
15 parallel arrangements of two resistors R1 and R2 and two neon lamps L1 and L2. This is the voltage testing circuit.

The two bias resistors R1, R2, arranged in series, serves as a pair of controlling devices, that allows the right voltage
20 to go to the right neon lamp L1, L2, thus illuminating it. The illustration in FIG. 6 shows the test probes 32, 35 inserted in a wall socket 60 of a 120 VAC receptacle.

R2 (33K) is the bias resistor for the 120 VAC neon lamp L1.
With the test probes 32, 35 inserted into the 120 VAC wall
socket 60, the ~~The lamp L1 will glow~~ ~~is now glowing~~.

5 When the test probes are inserted in a 240 VAC source or
outlet (not shown), the bias resistor R1 (220K) allows the
240 VAC neon lamp L2 to glow.

When not in use, the test circuit 80 should be switched to
10 position "B"U, which is also the off position for the
battery's power. FIG. 7 illustrates the actual assembly of
the device.

Referring now to FIG. 8, there is shown one particular
15 embodiment of the portable thermostatic controller and
circuit tester 10, wherein the project casing which houses
the thermostatic controller and circuit tester 10 has
specific dimensions. For example, in the embodiment of FIG.
8, the project casing which houses the thermostatic
20 controller and circuit tester 10 is 5 5/8 inches in length, 3
1/4 inches in width and 1 1/2 inches deep. The controller
leads extend 29 1/2 inches from the project casing. Further,
the test leads extend 44 inches from the casing 11'.

Abstract:

Thermostatic Controller and Circuit Tester is a new trouble shooting device, designed to improve the air conditioning technicians fault diagnostic capabilities. The device comes
5 equipped with two independent circuits and its own built in flashlight. The first circuit is the controller, which is outfitted with test leads with alligator clips controlled by four push on-push off switches. When attached to the thermostat wires or the air handlers connector block, it
10 allows the air conditioning system to be manually overridden, so as to determine and locate defects in the system. The next circuit, with detachable test leads and probes, performs line voltage and continuity tests.